







Pre-Task	<ul style="list-style-type: none"> <li>• Consider the task and follow safe job procedures, industry best practices, and legislative requirements.</li> <li>• Complete a hazard assessment and follow the required controls.</li> <li>• Ensure that the scaffold is inspected and tagged by a competent worker.</li> <li>• Follow Fall Protection Plan and controls while working at heights.</li> <li>• Maintain good housekeeping practices to prevent tripping.</li> </ul>
During	<ul style="list-style-type: none"> <li>• Ensure scaffold is built on firm ground or a solid sub-base.</li> <li>• Inspect and maintain safe limits of approach when working around overhead power lines.</li> <li>• Provide safe ladder access and ensure all guardrails and toe boards are installed as per requirements.</li> <li>• A free-standing scaffold's height must never exceed three times the minimum base dimension.</li> <li>• Always tie a scaffold into an existing structure according to requirements.</li> <li>• Minimize tools and equipment on a scaffold platform whenever possible.</li> </ul>
Post-task	<ul style="list-style-type: none"> <li>• Clean, sort, and secure scaffolding components when not in use.</li> <li>• Remove all defective equipment from service.</li> <li>• Maintain and record dates for scaffolding systems and self-retracting devices to complete inspection and or service.</li> </ul>

Task/Environment/Equipment	
Scaffolding	
Protective Measures	
SSHA	
Engineering	
Training	
SJP	
ERP	
PPE	

The information presented in this publication is intended for general use and may not apply to every circumstance. It is not a definitive guide to OHS legislation or industry standards. This does not relieve persons using this publication from their responsibilities under applicable legislation. The Alberta Construction Safety Association does not guarantee the accuracy of, nor assume liability for, the information presented here.